


NOTE:
 1. Rating: AC125V 5A/250V 3A
 2. Operating force: 25±10gf
 3. Mechanical Life: 1,000,000
 3. Electrical Life: 6000-10,000



Circuit Diagram

⑧	Shrapnel 2	1	Copper Alloy			
⑦	Shrapnel 1	1	Beryllium Copper			
⑥	Contact	1	Copper Alloy	Plating silver		
⑤	Lever	1	Stainless Steel			
④	Terminal	3	Copper Alloy	Plating silver		
③	Housing	1	PBT	Black		
②	Knob	1	PBT	Black		
①	Cover	1	PBT	Black		
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	ELECTRONICS CO.,LTD		
DRAWN	J.X.Zhang	2014/8/20	MICRO SWITCHS		
CHECKED			PART NO. K9-1910D		
APPROVALS			TITLE: MICRO SWITCHS		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	30~125 ±	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROD.	SHEET
	A		NEW				10~20 ±	±0.25						1 OF 1
							5~10 ±	±0.20		±2'				