


- Typical Specifications
1. Rating : 5A120V AC
 2. Insulation Resistance: 1,000M min
 3. Dielectric Strength: 1,500V RMS
 4. Operating Life : 30,000 cycles



Circuit Diagram

PART NO	vigor
1	300±100

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Copper	Plating silver	—
④	Contact	—	1	F.Ag/C5210	—	—
③	Base	—	1	PA	Black	—
②	Cover	—	1	SPCC	Plating Sn	—
①	Keystroke	—	1	PA	RED	—

APPROVALS		DATE	ELECTRONICS CO.,LTD	
DRAWN	JIANKUN.LIU	2015.05.25	Slide SWITCHS	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
—	A	—	NEW	—	—	—
TOLERANCES ARE			30~125H ±0.30	ANGLE	±2°	PROJ.
			10~30 ±0.20	UNIT: mm	SCALE: 1:1	PROJ.
			5~10 ±0.15	DRAWING NO.	—	SHEET 1 OF 1
			~5 ±0.10	PART NO.	K3-2391A	