



- Typical Specifications :
1. Rating : DC 12V 50mA
 2. Insulation resistance: $\geq 100M\Omega$
 3. Withstand voltage: AC 500V/1min
 4. Life: 100,000 Cycles Min.



Circuit Diagram

NO.1	
PART NO	H
D	3.5
F	5

NO.2	
PART NO	vigor
	3 180 \pm 30
	4 250 \pm 30
	5 350 \pm 50

NO.3-NO.4	
PART NO	NOTE
	01~99 SERIAL NUMBER

⑤ Terminal	—	4	Phosphor Bronze	Plating silver	—	
④ Contact	—	1	F.Ag/SUS	—	—	
③ Base	—	1	PA46	Black	—	
② Cover	—	1	SPCC	Plating Sn	—	
① Keystoke	—	1	PA46	White	—	
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE	—			
DRAWN		xu qi feng	2014.10.28	—		

OKHRO
ELECTRONICS CO.,LTD

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
—	B	—	1 修改型号为单弹20160927	—	—	—
—	A	—	NEW	—	—	—
TOLERANCES ARE						
		30~12.5	±0.30	ANGLE	±2°	DRAWING NO.
		10~30	±0.20			PART NO. K2-1156UP-□□□□-□□
		5~10	±0.15			SCALE: 1:1
		~5	±0.10			PROJ:
						SHEET 1 OF 1