



- Typical Specifications :
1. Rating : DC 12V 50mA
  2. Insulation resistance:  $\geq 100M\Omega$
  3. Withstand voltage: AC 500V/1min
  4. Life: 100,000 Cycles Min.



Circuit Diagram

NO.1	
PART NO	H
D	3.5
F	5

NO.2	
PART NO	vigor
3	180 $\pm$ 30
4	250 $\pm$ 30
5	350 $\pm$ 50

NO.3-NO.4	
PART NO	NOTE
01~99	SERIAL NUMBER

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Phosphor Bronze	Plating silver	—
④	Contact	—	1	F.Ag/SUS	—	—
③	Base	—	1	PA46	Black	—
②	Cover	—	1	SPCC	Plating Sn	—
①	Keystroke	—	1	PA46	White	—

APPROVALS		DATE
DRAWN	xu qi feng	2014.10.28

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	B		修改型号为单脚 20160927			
	A		NEW			

APPROVALS		TITLE:	
CHECKED		TACT SWITCHS	
TOLERANCES ARE		PART NO.	K2-1156SP-000W-00
30 $\pm$ 0.15	$\pm$ 0.30	SCALE:	1:1
10 $\sim$ 30	$\pm$ 0.20	UNIT:	mm
5 $\sim$ 10	$\pm$ 0.15	DRAWING NO.	
$\sim$ 5	$\pm$ 0.10	SHEET	1 OF 1



ELECTRONICS CO.,LTD