



**SPECIFICATIONS:**  
 Voltage Rating: 250V AC Min  
 Current Rating: 2.0A Min  
 Dielectric Strength: 1000V AC For 1Minute  
 Insulation Resistance: 1000Megohms Min  
 Contact Resistance: 30Milliohms Max  
 Operation Temperature: -55°C To +125°C  
 Product Withstanding Reflow Soldering: 260°C For 15s

Durability : 5000 Cycles  
 Normal Force At Working Position: 80g Min  
 Insertion Force: >3N  
 Insulator: High Temperature Thermoplastic  
 UL 94V-0 Black (LCP Black)  
 Contact: Beryllium Copper,  
 Gold Flash Over Nickel

PART NO.	
BC-8-3PD	BC-8-3P

② Terminal	12	Phosphor Bronze	Au Plated
① Housing	1	LCP	Black
ITEM	PART NAME	TER'NO.	QTY.
APPROVALS		DATE	
DRAWN	xu qi feng	2014.12.05	

ELECTRONICS CO.,LTD



TITLE: 电池座

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		增加弹片高度尺寸 NEW			
TOLERANCES ARE						
		30~12.5	±0.30	ANGLE		PROJ.
		10~30	±0.25			
		5~10	±0.20			
		~5	±0.15			
			±2'	DRAWING NO.		SHEET 1 OF 1